

Rated cross-section [mm <sup>2</sup> ]:	<b>35</b>
Rated current [A] [A]	<b>125</b>
Short-time withstand current [A]	<b>4200</b>
Rated voltage Ui [V]	<b>1000</b>
Rated impulse withstand voltage Uimp [V]	<b>8000</b>
Tightening torque [Nm]	<b>10 (35 mm<sup>2</sup>)</b>
Tightening torque [Nm]	<b>3 (16 mm<sup>2</sup>)</b>
Tool	<b>Inbus</b>
Assembly method	<b>TH 35 / on the plate</b>
IP code	<b>20</b>
Number of clamping points	<b>8</b>
Number of levels	<b>1</b>
End cover plate required	<b>NO</b>
Testing	<b>EN 60947-7-1</b>
Dimensions [mm] (width / height / length)	<b>29 / 46 / 77</b>
Weight [g]	<b>150</b>
Packing [pcs]	<b>1</b>

### **Conductor cross section**

Conductor cross-section – Input [mm <sup>2</sup> ]	<b>6 ÷ 35</b>
Conductor cross-section – Input [mm <sup>2</sup> ]	<b>1,5 ÷ 25</b>
Conductor cross-section – Output [mm <sup>2</sup> ]	<b>6 x 1,5 ÷ 25 (solid conductor)</b>
Conductor cross-section – Output [mm <sup>2</sup> ]	<b>4 x 1,5 ÷ 16 (flexible conductor with sl...</b>
Stripping length (Input) [mm]	<b>18 (35 mm<sup>2</sup>)</b>
Stripping length (Input) [mm]	<b>22 (16 mm<sup>2</sup>)</b>
Stripping length (Output) [mm]	<b>11 (16 mm<sup>2</sup> - top row)</b>
Stripping length (Output) [mm]	<b>23 (16 mm<sup>2</sup> - bottom row)</b>

