



Data subject to change without notice. Always confirm the data is correct from the seller.

# KL1X95N

## UL Listed Terminal Blocks

- **UL listed connector**
- Sales unit = 1 piece
- Bi-metal terminal suitable for Al (KL terminals) / Cu (KL and KC terminals) cables
- Available in grey, blue (N) and yellow/green (PE)
- Touchproof, IP20
- Housing and cover in polyamide
- Terminal material KL tin-coated, greased aluminium
- Environmentally friendly materials
- Durable laser markings

**UL CATALOGUE PAGE>>**

## Terminal Blocks

- **UL listed connectors, see link below**
- Bi-metal terminal suitable for Al (KL terminals) / Cu (KL and KC terminals) cables
- Available in grey, blue (N) yellow/green (PE), red (P) and black (M)
- 50 and 95 mm<sup>2</sup> connectors also available as 1-pole branching connector (3x) and 3-pole connector (3x1x)
- 1000 VAC and 1500 VDC
- Touchproof, IP20
- KC-terminals and KL1X16 models for DIN-rail mounting, refer to detailed product specifications
- KL-terminals (excl. KL1X16 models) for DIN-rail or base mounting, refer to detailed product specifications
- Housing and cover in polyamide
- Terminal material KL tin-coated, greased aluminium
- Terminal material KC steel and brass
- Environmentally friendly materials
- Durable laser markings
- Sales unit = 1 piece

## Product details

<b>SKU</b>	KL1X95N
<b>Al mm<sup>2</sup></b>	16 - 95
<b>Color</b>	N
<b>Cu mm<sup>2</sup></b>	16 - 95
<b>E-Number</b>	1942068
<b>EAN</b>	6419410378328
<b>In (Al) (A)</b>	200
<b>In (Cu) (A)</b>	245
<b>Key size</b>	Hex 6
<b>Mounting</b>	Screw / DIN
<b>Number of Conductors</b>	2
<b>Package size</b>	22
<b>Torque Al/Cu (Nm)</b>	12 (16 - 50 mm <sup>2</sup> ) / 22 (70 - 95 mm <sup>2</sup> )
<b>Un (V)</b>	1000
<b>Weight (lb/kg)</b>	0.212 / 0.096

## Dimensional drawing

