



Data subject to change without notice. Always confirm the data is correct from the seller.

KVKE 3125 L220AD12TLK12 SS

KVKE Switch fuses 20-630A

- **20-32 A:**
- 10×38 & BS fuse versions
- DIN rail and screw base mounting as standard
- Available as 3-pole and 4-pole version, 1-pole and 2-pole versions on request
- Handle LK10 and shaft L=180 mm included, suitable for 250 mm deep panel boards
- Fuse covers included
- Black or yellow/red handle, add Y/R to description
- **63-630 A:**
- DIN & BS fuse versions
- Four breaking points per phase
- Connecting silver rivets have a silver alloy 350 um thick, thus ensuring a long life expectancy and safe use in demanding conditions
- Compact size saves space
- Modular structure enables position of drive mechanism to be varied, mention when ordering
- Available as 1-, 2-, 3- and 4-pole (200-630 A also 6-pole)
- Black or yellow/red handle (add Y/R to description)
- Auxiliary contacts are easy to install
- Fuse covers included, terminal covers as accessory
- 63-160 A includes handle LK12 and shaft L=220 AD12/T
- 200-630 A includes handle LK14 and shaft LVK=228
- **Note!** Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector, **available here.**

Accessories

Handle & Shaft

Technical Data



Product details

SKU	KVKE 3125 L220AD12TLK12 SS
AC-21 400/415 V (A)	125 A
AC-21 690 V (A)	125 A
AC-22 400/415 V (A)	125 A
AC-22 690 V (A)	125 A
AC-23 400/415 V (A/kW)	125 A / 55 kW
AC-23 690 V (A/kW)	125 A / 110 kW
Cable Area to Switch Terminal (only Cu) (mm²) / Bolt size	6-70
E-Number	3662051
EAN	6419410286081
Number of Poles	3
Operation	Rotary
Switch type	Switch Fuse
Weight (kg)	1.664

Dimensional drawing

