

# KU 4315 SV

## KU Rotary switches and change-over switches 315-400A



Data subject to change without notice. Always confirm the data is correct from the seller.

- Made of halogen-free thermoplastic material. Materials have 100 % recyclability.
- Option for test position for testing auxiliary contacts while main contacts remain open. Note, only available on request.
- Reliable switch for demanding industrial applications
- Change-over switches: 'CO' included in type name
- Change-over switches with direct handle: 'CO SV' included in type name
- Change-over switches are always delivered with bridging bars
- Types without 'SV': Delivered with separate handle (**LKX 150**) and shaft (**LVK=228**)
- Available with yellow/red handle (**LKX 150 Y/R**) and a shaft of different length (100mm-500mm) on demand
- Types with 'SV': delivered with direct handle
- 400 A switch: AC-23 1000V 200 A
- Icw 690V (1s) 13,5kA
- R.M.S value 100 kA
- Auxiliary contacts available (**1.V160KU** or **2.V160KU**), up to 8 NC / 8 NO
- Terminal covers (LS400H and LS400F) and phase barriers (VS400) available
- Cable connectors for Al and Cu cables **available here.**

Technical Data

Accessories

Handle & Shaft

CE EAC



## Product details

<b>SKU</b>	KU 4315 SV
<b>AC-21 400/415 V (A)</b>	315 A
<b>AC-21 690 V (A)</b>	315 A
<b>AC-22 400/415 V (A)</b>	315 A
<b>AC-22 690 V (A)</b>	315 A
<b>AC-23 400/415 V (A/kW)</b>	315 A / 160 kW
<b>AC-23 690 V (A/kW)</b>	315 A / 315 kW
<b>Cable Area to Switch Terminal (only Cu) (mm<sup>2</sup>) / Bolt size</b>	M10
<b>E-Number</b>	3602937
<b>EAN</b>	6419410300312
<b>Number of Poles</b>	4
<b>Operation</b>	Front-operated
<b>Switch type</b>	Load Break Switch
<b>Weight (kg)</b>	2.49

## Dimensional drawing

