

KU 3800 SV

KU Rotary switches and change-over switches 630-800A



Data subject to change without notice. Always confirm the data is correct from the seller.

- Made of halogen-free thermoplastic material. Materials have 100 % recyclability.
- Option for test position for testing auxiliary contacts while main contacts remain open. Note, only available on request.
- Reliable switch for demanding industrial applications
- Change-over switches: 'CO' included in type name
- Change-over switches with direct handle: 'CO SV' included in type name
- Change-over switches are always delivered with bridging bars
- Types without 'SV': Delivered with separate handle (**LKX 150**) and shaft (**LVK=228**)
- Available with yellow/red handle (**LKX 150 Y/R**) and a shaft of different length (100mm-500mm) on demand
- Types with 'SV': delivered with direct handle
- 800 A switch: AC-23 1000V 400 A
- Icw 690V (1s) 28kA
- R.M.S value 100kA
- Auxiliary contacts available (**1.V160KU** or **2.V160KU**), up to 8 NC / 8 NO
- Terminal covers and phase barriers (**VS800**) available
- Cable connectors for Al and Cu cables **available here.**

Technical Data

Accessories

Handle & Shaft

CE EAC



Product details

SKU	KU 3800 SV
AC-21 400/415 V (A)	800 A
AC-21 690 V (A)	800 A
AC-22 400/415 V (A)	800 A
AC-22 690 V (A)	800 A
AC-23 400/415 V (A/kW)	800 A / 400 kW
AC-23 690 V (A/kW)	800 A / 800 kW
Cable Area to Switch Terminal (only Cu) (mm²) / Bolt size	M12
E-Number	3602884
EAN	6419410484005
Number of Poles	3
Operation	Rotary, with direct handle
Switch type	Load Break Switch
Weight (kg)	4.545

Dimensional drawing

