



Data subject to change without notice. Always confirm the data is correct from the seller.

# KU 363N

## KU Rotary switches and change-over switches 16-125A

- Compact size
- VV = change-over switch
- DIN-rail mounting
- 3-pole and 4-pole KU-switches as standard
- 2-pole upon request
- 6-pole and 8-pole versions consist of two 3-pole or 4-pole KU-switches connected by a parallel kit
- Switch technology by means of silver contacts ensures safe and durable operation
- Compatible with handles LK10 and LK11 (load break switches) and LK12 (change-over switches)
- Shafts L=100/200/300 AD11 and L=100/200/300 AD11/VT (load break switches) and L=100/200/300 AD12/VT (change-over switches)
- Tested according to IEC 60947-3
- Available with **CCC certificate**, mention when ordering
- **Note!** Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector, **available here**.

Technical Data

Accessories

Handle & Shaft



## Product details

<b>SKU</b>	KU 363N
<b>AC-22 400/415 V (A)</b>	63 A
<b>AC-22 690 V (A)</b>	63 A
<b>AC-23 400/415 V (A/kW)</b>	40 A / 22 kW
<b>AC-23 690 V (A/kW)</b>	40 A / 37 kW
<b>Cable Area to Switch Terminal (only Cu) (mm<sup>2</sup>) / Bolt size</b>	2.5-35
<b>E-Number</b>	3600723
<b>EAN</b>	6419410214602
<b>Number of Poles</b>	3
<b>Operation</b>	Rotary
<b>Switch type</b>	Load Break Switch
<b>Weight (kg)</b>	0.2

## Dimensional drawing

